



fiorentini

WWW.FIORENTINISPA.COM

PINKY 26/32




We clean the world.

Noi puliamo il mondo.

PINKY 26/32



SPECIFICHE PRINCIPALI / TECHNICAL SPECIFICATIONS PRINCIPALES CARACTERISTIQUES TECHNIQUES	PINKY 26B	PINKY 32B	PINKY 26RB
Larghezza utile di lavoro / Scrubbing width Largeur de nettoyage	650 mm	850 mm	650 mm
Rendimento orario max. / Cleaning capacity up to Rendement jusqu'à	3250 m²/h	4250 m²/h	3250 m²/h
Autonomia di lavoro max. / Operating range Autonomie	4 - 5 h	3,5 - 4,5 h	4 - 5 h
Capacità serbatoio soluzione / Solution tank capacity Capacité réservoir solution	90 L	90 L	90 L
Capacità serbatoio recupero / Recovery tank capacity Capacité réservoir recuperation	77 L	77 L	77 L
Velocità di avanzamento / Forward speed Vitesse d'avancement	Km/h 0 - 5	Km/h 0 - 5	Km/h 0 - 5
Pendenza superabile a pieno carico / Max. slope Pente max. surmontable	10 %	10 %	10 %
Depression / Water lift Dépression	135 mBar	135 mBar	135 mBar
Pressione testata spazzole / Brush pressure Pression des brosses	30/60 Kg	30/60 Kg	30/60 Kg
Rumorosità / Noise level Bruit	73 dB	73 dB	73 dB
SPECIFICHE ALIMENTAZIONE / POWER SPECIFICATIONS DONNEES DE L'ALIMENTATION	PINKY 26B	PINKY 32B	PINKY 26RB
Motore trazione / Traction motor Moteur traction	transaxle 24v x 200w 120rpm 10A	transaxle 24v x 200w 120rpm 10A	transaxle 24v x 200w 120rpm 10A
Motore di aspirazione / Vacuum motor Moteur d'aspiration	24v/500w conv.	24v/500w conv.	24v/500w conv.
Motore spazzola con riduttore / Brush motor with reduction gear / Moteur des brosses avec réducteur	1/10 2 x 24v / 300w	1/10 2 x 24v / 650w	1 x 24v / 650w
Alimentazione / Voltage Alimentation	24v 4x 6v 240 A/h	24v 4x 6v 240 A/h	24v 4x 6v 240 A/h
DIMENSIONI E PESI / DIMENSIONS & WEIGHT DIMENSIONS ET POIDS	PINKY 26B	PINKY 32B	PINKY 26RB
Misure: L x l x h / Measures: L x w x h Mesures: L x l x h	mm 1330 x 700 x 1070	mm 1350 x 850 x 1070	mm 1330 x 700 x 1070
Numero diametro spazzole / Number of brushes and diameter / Nombre et diamètre des brosses	2 x Ø 330 mm	2 x Ø 410 mm	n° 2 rulli n° 2 cylindr. br. n° 2 br. cylindr. Ø110 L: 650
Larghezza tergipavimento / Squeegee width Largeur du suceur	890 mm	980 mm	890 mm
Peso macchina a vuoto (senza batteria/acqua/operatore) Weight of the machine (without batteries/water/operator) Poids de la machine (sans batteries/eau/ opérateur)	118 Kg	126 Kg	118 Kg
Peso batterie (apx.) / Weight of the batteries (approx.) Poids des batteries (approx.)	4 x 26 Kg	4 x 26 Kg	4 x 26 Kg



fiorentini
WWW.FIORENTINISPA.COM

*We clean the world.
Noi puliamo il mondo.*

www.fiorentinispa.com - sales@ingfiorentini.it

SEDE AMM. E STABILIMENTI

50030 PIANCANDOLI (FI) - Loc. ROMBOLA - via piancandoli, 1896 - Tel. +39 055.8173610 - Fax +39 055.817144

50033 PIETRAMALA (FI) - via lame, 70/b - Tel. +39 055.813447 - Fax +39 055.813504

40024 CASTEL SAN PIETRO (BO) - via ca bianca, 231/c - Tel. +39 051.941743 - Fax +39 051.6942400

FILIALI

20132 MILANO - Via Palmanova, 211/A - Tel. +39 02.27207783 - 2564810 - Fax +39 02.2592779

00012 GUIDONIA MONTECELIO (ROMA) - Via Pontecorvo, 20 - Tel. +39 0774.357184 - Fax +39 0774.353419